

Appl. No. 10/800,371  
Amdt. dated August 7, 2007  
Response to Notice of Allowance May 29, 2007

PATENT

**Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

1. (Previously Presented) An apparatus for processing a supervisory signal for optical network applications, the apparatus comprising:
  - a subcarrier transmission system configured to receive a first supervisory signal and output a second supervisory signal;
  - an electrical-to-optical conversion system configured to receive the second supervisory signal and a first data signal and output a first optical signal;
  - an optical-to-electrical conversion system configured to receive the first optical signal and output a first electrical signal and a second data signal;
  - a subcarrier reception system configured to receive the first electrical signal and output a third supervisory signal;
  - wherein the second supervisory signal is associated with a first subcarrier frequency;
  - wherein the first data signal is associated with a first data bandwidth, the first data bandwidth including a first data frequency, at the first data frequency a power density of the first data signal substantially equal to zero;
  - wherein a ratio of the first subcarrier frequency to the first data frequency ranges from 0.8 to 1;
  - wherein the first optical signal is associated with a perturbation to the first data signal, the perturbation being smaller than or equal to 1 dB;
  - wherein the first optical signal is associated with a signal-to-noise ratio for the second supervisory signal, the signal-to-noise ratio for the second supervisory signal being larger than or equal to 20 dB;

Appl. No. 10/800,371

PATENT

Amdt. dated August 7, 2007

Response to Notice of Allowance May 29, 2007

wherein the first supervisory signal is associated with a first subcarrier data rate larger than 1 Mbps.

2. (Original) The apparatus of claim 1 wherein the first subcarrier signal is associated with the first subcarrier data rate larger than 5 Mbps.

3. (Canceled)

4. (Original) The apparatus of claim 1 wherein the first data frequency is a maximum frequency associated with the first data bandwidth.

5. (Original) The apparatus of claim 4 wherein the first data frequency is substantially equal to 2.5 GHz and the first subcarrier frequency is substantially equal to 2.4 GHz.

6. (Original) The apparatus of claim 5 wherein the first data signal is associated with a non-return to zero format and a first data rate substantially equal to or smaller than 2.5 gigabits per second.

7.-18. (Canceled)

19. (Previously Presented) A method for processing a supervisory signal for optical network applications, the method comprising:

- receiving a first supervisory signal;
- processing information associated with the first supervisory signal;
- outputting a second supervisory signal based on at least information associated with the first supervisory signal;
- receiving the second supervisory signal and a first data signal;
- processing information associated with the second supervisory signal and the first data signal;
- outputting a first optical signal based on at least information associated with the second supervisory signal and the first data signal;

Appl. No. 10/800,371

PATENT

Amdt. dated August 7, 2007

Response to Notice of Allowance May 29, 2007

receiving the first optical signal;  
processing information associated with the first optical signal;  
outputting a first electrical signal and a second data signal based on at least  
information associated with the first optical signal;  
receiving the first electrical signal;  
processing information associated with the first electrical signal;  
outputting a third supervisory signal;  
wherein:  
the second supervisory signal is associated with a first subcarrier  
frequency;  
the first data signal is associated with a first data bandwidth, the first data  
bandwidth including a first data frequency, at the first data frequency a power density of  
the first data signal substantially equal to zero;  
a ratio of the first subcarrier frequency to the first data frequency ranges  
from 0.8 to 1;  
the first data frequency is a maximum frequency associated with the first  
data bandwidth;  
the first data frequency is substantially equal to 2.5 GHz and the first  
subcarrier frequency is substantially equal to 2.4 GHz;  
the first data signal is associated with a non-return to zero format and a  
first data rate substantially equal to or smaller than 2.5 gigabits per second;  
wherein the first optical signal is associated with a perturbation related to  
the first data signal, the perturbation being smaller than or equal to 1 dB, the first optical  
signal is associated with a signal-to-noise ratio for the second supervisory signal, the  
signal-to-noise ratio for the second supervisory signal being larger than or equal to 20 dB.

20. (Original) The method of claim 19 wherein the first supervisory signal is  
associated with a first supervisory data rate larger than 1 Mbps.

Appl. No. 10/800,371

PATENT

Amdt. dated August 7, 2007

Response to Notice of Allowance May 29, 2007

21. (Currently Amended) The ~~apparatus~~method of claim 20 wherein the first supervisory data rate is about 5 Mbps.

22.-30. (Canceled)